

## A400/800/1200 Series Analog Card Datasheet



- High performance with low price
- Modular Design: Up to 4, 8 or 12 FXS-100/FXO-100 or mixed FXS/FXO ports per card. Each port can be set as FXO or FXS via plugging different module in it
- LEDs display the board's status
- Scalable: Just adding more cards to extend the system
- Easy to use: the modules are Pin to Pin compatible with Digium's X100M and S100M. Users are also able to apply Digium's X100M/S100M modules on this card, or setup our FXO-100/ FXS-100 modules on TDM400P
- Worldwide usable: Configurable line interface to meet global telephone line interface requirements
- RoHS compliant
- ► Certificates: CE, FCC, A-Tick
- ► trixbox <sup>TM</sup> Officially Certified
- ► Elastix<sup>®</sup> Officially Certified

Operating System Linux (all versions, releases and distributions from 1.0 up)



- ► RAM 128 + MB Linux
- ► Kernel 2.4.X or 2.6.X or 3.X
- ► CPU 800+ MHZ
- ► Mini PCI, PCI or PCI-E slot



- Temperature:  $0 \sim 50^{\circ}$ C (Operation)
  - -40 ~125°C (Storage)
- 10~90% NON-CONDENSING ► Humidity:



OpenVox A400/800/1200 series analog card delivers great voice quality in the telephony systems. With interchangeable FXS/FXO-100 module, one module allows an analog phone or PSTN line, can eliminate the requirements for separate channel banks or access gateways.

The A400/800/1200 cards which with PCI or PCI-E contain 4, 8, 12 module banks respectively. The cards may be filled with up to 4, 8 or 12 FXO or FXS modules enabling the creation of any combination of ports. Scaling of an analog card solution is accomplished by simply adding additional cards.

A400/800/1200 series analog card works well with Asterisk<sup>®</sup>, Elastix<sup>®</sup>, FreeS-WITCH<sup>™</sup>, PBX in a Flash, trixbox<sup>®</sup>, Yate<sup>™</sup> and IPPBX/IVR projects as well as other Open Source and proprietary PBX, Switch, IVR, and VoIP gateway applications.

Pictures Items							
Products	A400M		A400P	A400E	A800P	A800E	A1200P
	A400MM	A400MS					
Bus Type	Mini PCI 1.0		PCI 2.2+	PCI-E 1.0+	PCI 2.2+	PCI-E 1.0+	PCI 2.2+
Ports	4 RJ11		4 RJ11	4 RJ11	8 RJ11	8 RJ11	3 RJ45
FXS	FXS-100		FXS-100	FXS-100	FXS-100	FXS-100	FXS-100
FXO	FXO-100		FXO-100	FXO-100	FXO-100	FXO-100	FXO-100
Echo Cancellation	N/A		N/A	N/A	N/A	N/A	N/A
Dimensions (mm)	59.6×44.6×10	11.2×11.3×1.3	136.3×101×16	136.3×111.5×16	246.7×106.7×16	246.7×111.4×16	312×106.7×16
Weights (g)	14	64	82	89	133	124	161
DTMF Detection	$\checkmark$		$\checkmark$	$\checkmark$	$\checkmark$	$\checkmark$	$\checkmark$
Caller ID	$\checkmark$		$\checkmark$	$\checkmark$	$\checkmark$	$\checkmark$	$\checkmark$
Loopstart Signaling	$\checkmark$		$\checkmark$	$\checkmark$	$\checkmark$	$\checkmark$	$\checkmark$
Bus Master DMA	$\checkmark$		$\checkmark$	$\checkmark$	$\checkmark$	$\checkmark$	$\checkmark$
Voltage Detection	$\checkmark$		$\checkmark$	$\checkmark$	$\checkmark$	$\checkmark$	$\checkmark$

- **Target Applications**
- Small and Medium Business (SMB)
- Gateway Termination to analog
- Channel Bank Replacement / Alternative
- Small Office Home Office (SOHO)